

23 Giugno 2012

Omnicon Schneider Wireless Partner

Dal 2007 è attiva la partnership con Control Microsystems, azienda Canadese leader nei sistemi di automazione industriale, controllo e SCADA. La collaborazione con Control Microsystems ha portato Omnicon a diventare unico distributore per l'Italia dei suoi prodotti. Nel 2011 Schneider Electric ha acquisito Control Microsystems e Omnicon ha assunto il ruolo di "Schneider Wireless Partner" grazie alle sue competenze nei sistemi wireless di telemetria e telecontrollo.

Le soluzioni offerte da Omnicon si basano sulla estesa gamma di prodotti Schneider, dai sistemi radio, sensori wireless, al software Scada e sistemi RTU.

Sistemi Radio Trio

Il trasferimento di dati wireless tra i dispositivi di campo remoti e il sistema SCADA è parte integrante di qualsiasi sistema SCADA. La serie di Radio TRIO, licenziate e non, affronta le molteplici sfide annesse alla comunicazione wireless, fornendo l'affidabilità e la flessibilità sia nella selezione dei prodotti che nella funzionalità.

Strumentazione Wireless Accutech

Schneider Electric porta l'innovazione wireless in primo piano con la linea di sensori wireless Accutech. La linea di prodotti include una selezione di sensori di campo e di radio che utilizzano la banda 869MHz per fornire in modo sicuro i dati critici di processo agli altri componenti del sistema SCADA.

ClearScada Management Software

ClearSCADA è la piattaforma software di controllo di Schneider Electric per la raccolta, lo stoccaggio, il recupero e la visualizzazione dei dati critici di un sistema SCADA.

SCADAPack PLC&RTU

La serie SCADAPack of Programmable Logic Controllers (PLC), prevede Remote Terminal Unit (RTU) e funzioni per l'utilizzo in applicazioni di telemetria e SCADA. Questi prodotti di alta qualità includono una gamma completa di soluzioni flessibili wireless.

GAS Flow & Pressure

Schneider Electric offre prodotti per la misura di flussi e pressione, compreso il rivoluzionario RealFLO gas computer con PLC integrato, e i prodotti

[Ritorno all'Indice](#)

e 2012

Desigo V5: Innovations from Siemens increase building efficiency

The Siemens Building Technologies Division has introduced version 5 of its Desigo building automation system. Its innovative products such as Total Room Automation as well as efficiency features, like RoomOptiControl and Eco Monitoring, give building operators and users an active role in energy management, leading to permanent reductions in energy and maintenance costs. A state-of-the-art building automation system is always optimized for energy-efficient operation. However, these optimized settings may start to drift over time. One of the underlying causes is often a lack of transparency for users who simply don't know how the setpoint changes they make can impact energy consumption. This is particularly true for air-conditioned rooms which are also equipped with lighting and sun protection controls. The new version of Desigo keeps room users and building operators apprised of the building's efficiency status. Feedback to users is given using the innovative Green Leaf display, adapted to the expertise and control options of each user group. The system makes it possible to change settings if needed to restore optimal energy efficiency. A study by Technische Universität München (TUM) indicates that by actively involving operators and users in the energy management of a building, energy consumption can be reduced by up to 25% without affecting comfort.

Total Room Automation offers energy savings without reducing comfort

The open, programmable room automation range Desigo Total Room Automation (TRA) is a holistic solution encompassing the HVAC, lighting and shading disciplines. Desigo TRA uses an innovative efficiency feature called RoomOptiControl. It automatically detects unnecessary energy consumption in the room and notifies users by changing the color of the Green Leaf icon on the QMX3 room control unit: If room operations are energy efficient, this icon is green. If settings made by a room user lead to unnecessary energy consumption, the icon turns red. To reset room control to energy efficient operation, the user simply presses the display and the Green Leaf icon returns to green.

Using BACnet/IP, PXC3 room automation stations—also part of the TRA package—are integrated seamlessly into the PX automation level with its primary systems (heating generators, HVAC main units and cooling generators). The primary systems are controlled directly through the demand signals from the rooms. This means that the primary systems are only turned on if needed and their operation is adjusted so it meets the room requirements without exceeding them. One room automation station can cover multiple rooms. TRA offers complete integration of KNX, DALI and EnOcean devices; existing or new sensors and actuators from Siemens can be incorporated as well.

Eco Monitoring to reduce energy consumption and wear

Eco Monitoring is another innovative efficiency feature of Desigo. It monitors ongoing operations of HVAC systems based on energy-related quality condition indicators such as readings from temperature, humidity and pressure sensors, runtime, switching behavior and operational performance of the systems. Should deviations from the target state, inefficient operations or increased energy consumption occur, the building operator is notified via the Green Leaf display on the Desigo Insight management station. Current and future international standards (such as EN 15323:2007) require such a feature in order to optimize building operations over the long term.

Desigo Eco Monitoring not only helps optimize energy consumption, it also reduces wear.

Thanks to its dynamic behavior and timely reporting, the Eco Monitoring feature recognizes unfavorable system operations early on, allowing operators to intervene immediately before any negative impact occurs. If desired, operators can choose to be notified of unusual events via

text messaging (SMS), fax or e-mail.

Expanded networking of the automation level

Starting with version 5, Desigo also offers expanded end-to-end networking of the automation level. Enhanced support for communications standards ensures efficient system integration.

The PXC series of compact automation stations has a higher number of universal inputs/outputs, which makes them much more flexible. To protect existing investments, different device generations, such as PTM and TX I/O modules and RXC room controllers, can be used in parallel on the same PX automation station.